

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name: Chlorpromazine-D3 maleate solutionProduct Number: C-107Brand: CerilliantIndex-No.: 603-001-00-X)	Relevant identified us	es	of the substance or mixture and uses advised against
Product Number : C-107		Index-No.	:	603-001-00-X
Chiorpromazine-D3 maleate solution		Brand	:	Cerilliant
Product name : Chlorpromazine-D3 maleate solution		Product Number	:	C-107
		Product name	:	Chlorpromazine-D ₃ maleate solution

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses	:	Laboratory chemicals,	Synthesis	of substances
-----------------	---	-----------------------	-----------	---------------

1.3 Details of the supplier of the safety data sheet

Company	: Cerilliant Corporation
	811 Paloma Drive, Suite A
	ROUND ROCK TX 78665
	UNITED STATES

1.4 Emergency telephone number

Emergency Phone #	: 800-424-9300 CHEMTREC (USA) +1-703-
	527-3887 CHEMTREC (International) 24
	Hours/day; 7 Days/week

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 2), H225 Acute toxicity, Oral (Category 3), H301 Acute toxicity, Inhalation (Category 3), H331 Acute toxicity, Dermal (Category 3), H311 Specific target organ toxicity - single exposure (Category 1), H370

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Danger

Pictogram

Signal word Hazard statement(s) H225

H225 Highly flam H301 + H311 + H331 Toxic if swa

Cerilliant - C-107

Highly flammable liquid and vapour. Toxic if swallowed, in contact with skin or if inhaled.

Page 1 of 11



H370	Causes damage to organs.
Precautionary statement(s)	
P210 , ()	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ ventilating/ lighting equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P264	Wash skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P303 + P361 + P353	IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P307 + P311	IF exposed: Call a POISON CENTER or doctor/ physician.
P322	Specific measures (see supplemental first aid instructions on this label).
P330	Rinse mouth.
P361	Remove/Take off immediately all contaminated clothing.
P363	Wash contaminated clothing before reuse.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Component		Classification	Concentration			
Methanol						
CAS-No. EC-No. Index-No.	67-56-1 200-659-6 603-001-00-X	Flam. Liq. 2; Acute Tox. 3; STOT SE 1; H225, H301, H331, H311, H370	>= 90 - <= 100 %			
Registration	01-2119433307-44- XXXX					

For the full text of the H-Statements mentioned in this Section, see Section 16.

Cerilliant - C-107

Page 2 of 11



SECTION 4: First aid measures

4.1 Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.

In case of eye contact

Flush eyes with water as a precaution.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

- **4.2 Most important symptoms and effects, both acute and delayed** The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11
- **4.3 Indication of any immediate medical attention and special treatment needed** No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

- **5.2 Special hazards arising from the substance or mixture** Carbon oxides
- **5.3** Advice for firefighters Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear respiratory protection. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

For personal protection see section 8.

6.2 Environmental precautions Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

Cerilliant - C-107

Page 3 of 11



6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wetbrushing and place in container for disposal according to local regulations (see section 13).

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist. Use explosion-proof equipment.Keep away from sources of ignition - No smoking.Take measures to prevent the build up of electrostatic charge. For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store under inert gas. hygroscopic

Recommended storage temperature -20 °C Storage class (TRGS 510): 3: Flammable liquids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
Methanol	67-56-1	TWA	200 ppm	USA. ACGIH Threshold Limit Values (TLV)
	Remarks	Headache Nausea Dizziness Eye damage Substances for which there is a Biological Exposure I or Indices (see BEI® section) Danger of cutaneous absorption		
		STEL	250 ppm	USA. ACGIH Threshold Limit Values (TLV)
		Headache Nausea Dizziness Eye damage Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Danger of cutaneous absorption		

Cerilliant - C-107

Page 4 of 11



TWA	200 ppm 260 mg/m3	USA. NIOSH Recommended Exposure Limits
Potential f	or dermal absor	ption
ST	250 ppm 325 mg/m3	USA. NIOSH Recommended Exposure Limits
Potential f	or dermal absor	
TWA	200 ppm 260 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
The value	in mg/m3 is app	proximate.
C 1,000 ppm Cali limi con		California permissible exposure limits for chemical contaminants (Title 8, Article 107)
Skin	•	
PEL	200 ppm 260 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
Skin	1	
STEL	250 ppm 325 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
Skin		

Biological occupational exposure limits

Component	CAS-No.	Parameters	Value	Biological specimen	Basis		
Methanol	67-56-1	Methanol	15 mg/l	Urine	ACGIH - Biological Exposure Indices (BEI)		
	Remarks	End of shift (osure ceases)				

8.2 Exposure controls

Appropriate engineering controls

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

Personal protective equipment

Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Cerilliant - C-107

Page 5 of 11



Full contact Material: butyl-rubber Minimum layer thickness: 0.3 mm Break through time: 480 min Material tested:Butoject® (KCL 897 / Aldrich Z677647, Size M)

Splash contact Material: Nitrile rubber Minimum layer thickness: 0.4 mm Break through time: 30 min Material tested:Camatril® (KCL 730 / Aldrich Z677442, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a fullface respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a)	Appearance	Form: liquid
b)	Odour	No data available
c)	Odour Threshold	No data available
d)	рН	No data available
e)	Melting point/freezing point	No data available
f)	Initial boiling point and boiling range	64 - 65 °C 147 - 149 °F at 1.013 hPa
g)	Flash point	9.7 °C (49.5 °F) - closed cup
h)	Evaporation rate	No data available
i)	Flammability (solid, gas)	No data available

Cerilliant - C-107

Page 6 of 11



	j)	Upper/lower flammability or explosive limits	Upper explosion limit: 36 %(V) Lower explosion limit: 6 %(V)
	k)	Vapour pressure	No data available
	I)	Vapour density	No data available
	m)	Relative density	0.791 g/cm3 at 20 °C (68 °F)
	n)	Water solubility	No data available
	o)	Partition coefficient: n-octanol/water	No data available
	p)	Auto-ignition temperature	No data available
	q)	Decomposition temperature	No data available
	r)	Viscosity	No data available
	s)	Explosive properties	No data available
	t)	Oxidizing properties	No data available
9.2	Oth	ner safety informatio	n

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Heat, flames and sparks. Extremes of temperature and direct sunlight.

10.5 Incompatible materials

Acids, Oxidizing agents, Alkali metals, Strong oxidizing agents, Strong acids, Acid chlorides, Acid anhydrides, Reducing agents, Strong reducing agents, Phosphorus halides

10.6 Hazardous decomposition products Other decomposition products - No data available Hazardous decomposition products formed under fire conditions. - Carbon oxides In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity No data available

Inhalation: No data available

Cerilliant - C-107

Page 7 of 11



Dermal: No data available

No data available

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation No data available

Respiratory or skin sensitisation No data available

Germ cell mutagenicity No data available

Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

- ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.
- NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure No data available

Specific target organ toxicity - repeated exposure No data available

Aspiration hazard

No data available

Additional Information

RTECS: Not available

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Methyl alcohol may be fatal or cause blindness if swallowed., Cannot be made nonpoisonous., Effects due to ingestion may include:, Nausea, Headache, Vomiting, Gastrointestinal disturbance, Dizziness, Weakness, Confusion.

Central nervous system - Breathing difficulties - Based on Human Evidence

Cerilliant - C-107

Page 8 of 11



SECTION 12: Ecological information

12.1 Toxicity

No data available

- **12.2 Persistence and degradability** No data available
- **12.3 Bioaccumulative potential** No data available
- **12.4 Mobility in soil** No data available
- 12.5 Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted
- **12.6 Other adverse effects** No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging

Dispose of as unused product.

SECTION 14: Transport information

DOT (US)

UN number: 1230 Class: 3 Packing group: II Proper shipping name: MethanolSOLUTION

Reportable Quantity (RQ): Poison Inhalation Hazard: No

IMDG

UN number: 1230 Class: 3 (6.1) Packing group: II Proper shipping name: METHANOLSOLUTION

EMS-No: F-E, S-D

ΙΑΤΑ

UN number: 1230 Class: 3 (6.1) Packing group: II Proper shipping name: MethanolSOLUTION

Cerilliant - C-107

Page 9 of 11



SEC	TION 15: Regulatory information					
	SARA 302 Components No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.					
	SARA 313 Components The following components are subject to reporting levels established by SARA Title III, Section 313:					
	Methanol	CAS-No. 67-56-1	Revision Date 2007-07-01			
	SARA 311/312 Hazards Fire Hazard, Acute Health Hazard, Chronic Health Hazar	ď				
	Massachusetts Right To Know Components					
	Methanol	CAS-No. 67-56-1	Revision Date 2007-07-01			
	No components are subject to the Massachusetts Right	to Know Act.				
	Pennsylvania Right To Know Components Methanol	CAS-No. 67-56-1	Revision Date 2007-07-01			
	Methanol	CAS-No. 67-56-1	Revision Date 2007-07-01			
	New Jersey Right To Know Components Methanol	CAS-No. 67-56-1	Revision Date 2007-07-01			
	California Prop. 65 Components WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.Methanol	CAS-No. 67-56-1	Revision Date 2012-03-16			

SECTION 16: Other information

Further information

Copyright 2018 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See

Cerilliant - C-107

Page 10 of 11



www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 6.1

Revision Date: 07/02/2019

Print Date: 03/30/2021

Cerilliant - C-107

Page 11 of 11

